



全方位触控解决方案提供商

TouchWo
触控·人机交互系统

Capacitive All In One PC

13.3 inches Capacitive Touch Panel

Technical Specification

(Model:TD133-A01)

Product Introduction



NOTE: Standard layout is wall mount, and the desktop bracket is optional.

Version V1.72

We apologize that if something is changed without notice.

<http://touchwo.en.alibaba.com/>



I. Introduction

The capacitive touchscreen all-in-one PC is the most convenient, simple, natural, practical interactive device, which gathers the strengths of touch technology, computer technology, multimedia technology, audio technology, network technology, industrial plastic arts, mechanical manufacturing technology, streamlined integration of design, etc., with a pure flat product structure, together with the excellent performance of touch experience and fast completion of information query and display, really easy to use interactive features.

Touchwo technology "TouchWo" brand capacitive all-in-one pc has been widely used in many occasions, such as car showroom, brand monopoly, hotel lobby, fairs, company showrooms, supermarkets, banks, government units and so on. We have focused on research and development production of touch products for many years, so that our products are more competitive than counterparts in both technology and practical applications.

II、Product Characteristic

1. Structure Design:

- (1) Pure flat structure, ergonomic design, slim and beautiful, streamlined shape, sophisticated technology;
- (2) Display, touch, PC system integration slim design;

2. Effect:

- (1) Using the newly developed projective capacitive screen, supports 10 point touch, handwriting and multi-point gesture;
- (2) Touch speed is less than 3ms, good accuracy, ease of use and easy to maintain;
- (3) Anti-light interference, to ensure the accuracy of operation (can be used as usual under bright light);

3. Good scalability: Flexible configuration, can expand the installation of customer demand for a variety of functional accessories;

4. High safety: Aluminum alloy + sheet metal structure, no sharp edges, wear resistant and anti-corrosive paint process, overall explosion-proof design design;



5. Stable performance: advanced design ideas, strict production process, stable and reliable product quality, low failure rate;
6. Simple installation: power a key switch, dispense with on-site installation and commissioning.

III、Applications

- Public places: subways, airports, bookstores, parks, exhibition halls, stadiums, museums, convention centers, ticket agents, talent market, lottery centers, hospitals, schools, telecommunications, post offices and so on;
- Entertainments: cinemas, gyms, holiday resorts, clubs, foot sauna, bars, cafes, beauty salons, golf courses and so on;
- Financial institutions: banks, securities, funds, insurance companies, pawn shops and the like;
- Commercial organization: shopping malls, chain stores, supermarkets, speciality stores, hotels, restaurants, travel agencies, pharmacies, etc;
- Properties: apartments, villas, offices, commercial buildings, model houses, sales offices and so on.

IV、Product Specifications

1、Touch screen parameters	
Touch screen type	Projected capacity touch screen
Response time	< 5ms
Touch points	Standard 10-point touch, Zooming in/out pictures by multi-point
Touch recognition	> 1.5mm(Finger, touch pen opaque objects)
Scanning rate	200 Hz
Scanning accuracy	4096×4096
Communication	Full-Speed USB 2.0, 3.0
Theory Clicks	More than 50 million times
Operating current / voltage	180Ma/DC+5V±5%
Anti-light interference	Sunlight, incandescent, fluorescent and other light during normal use change
Touch data output	Coordinate output
Surface hardness	Physical steel Mohs 7 explosion-proof glass



Operating System Compatibility	Windows 7/ Windows 8 / Windows XP / Linux /MAC OS /Android
Firmware	USB upgraded Support
Drive	Free drive, plug and play
2、LED screen parameters	
Screen Type	A-Si,TFT-LCD back-light, LED .A-type
Resolution	1920*1080P
Brightness	$\geq 330 \text{ cd/m}^2$
Contrast ratio	$\geq 700: 1$
Response time	25 (Typ.)(Tr+Td) ms
Number of colors	262 K (6-bit),CIE 1931 60%
Refresh rate	60Hz
Viewing angle	85/85/85/85(Typ.) CR ≥ 10) left/right/up/down
Life time	> 50000 hours
3、Display parameters (as a touch display only partially used)	
Power Interface	12V
Comb filter	3D COMB filter
VGA input(15-pin D-Sub)	1
High-definition multimedia interface (HDMI)	1
USB input	1
4、Power supply parameters	
Input Power	110—240V AC 50/60Hz
Output power	12V 4A
Overall power consumption	< 60W
Standby power consumption	< 0.5W
5、Working environment	
Operating temperature	0℃-38℃
Working humidity	0% - 90%
Storage temperature	-40℃-85℃
Storage humidity	10% - 95%
6、Standard Accessories	
Instructions	Electronic file specification
AC Power line	1 pc
Power Adapter	1 pc (Inbuilt power with AC power line 1 pc only)
Wall mount	1 set



Warranty Card	1 set
Certificate	1 set
WIFI	1 pc (standard with computer)


V、Computer system

Project	Touchscreen Monitor	Android	X86 Elite Version	Custom Design
Chip	Same as display parameters	Quad-core RK3188 /Octa core RK3368	X86 standard: Intel Celeron Quad core Z8300/8350	available
Ram		2G	4G	
Hard Disk		Flash 8G, scalable	32G/64G	
Graphics		Android HD	Core Graphics	
Definition	720P/1080P			
Operating System		Octa core Android 5.1. Kernel version 3.0.2	Standard Windows 10, Windows 7 supported by motherboard N3160/DM133	
NIC	Integrated 10/100 / 1000M adaptive network card, wireless network card 802.11a / b / g / n			
Input Power	110-240V AC 50/60Hz			

VI、size

Inch	13.3" (Diagonal 337.82mm)
display size	165×293.4mm (16: 9)
Machine size (width * height * thickness)	336.4 (W) × 214 (H) × 30.8 (T) mm
Package size (width * height * thickness)	490 (W) × 295 (H) × 145 (T) mm
Mounting bracket	Standard wall rack (0.48kg) , or desktop base
The back wall with holes for connection machine (length * width)	100×100 mm
Wall screw specifications	M4
Net weight	Touch monitor 1.84 kg all-in-one PC 1.96 kg
G.W (packaging)	3.82 kg

VII、Whole structure diagram:





VIII、Product detail chart





IX、Product design / product effect diagram

All-black, black panel, frame and back shell.



Black-Silver, black panel and back shell, silver frame.




Other colors could be customized, details please to contact our sales.





X. The Real Figure



XI、Product Accessories

<http://touchwo.en.alibaba.com/>



standard configuration:
Wall bracke/Simple desktop
/Embedded bracket
(choose one in three)
The other 2 stlyes for sell.





XII、Product Ports

Touch Monitor



Windows OS



2 com ports can be added

Android OS



Remark:13.3 inches' interfaces in on the bottom